



HOWARD WIRE CLOTH CO.

Stainless Steel Bolting Cloth

| Mesh Per Linear Inch | Wire Diameter Inches | Width of Opening Inches | Open Area Percent | Weight LBS./ 100 SQ. FT. |
|----------------------|----------------------|-------------------------|-------------------|--------------------------|
| 16 | .0090 | .0535 | 73.3% | 8.6 |
| 18 | .0090 | .0466 | 70.2% | 9.5 |
| 20 | .0090 | .0410 | 67.2% | 10.5 |
| 22 | .0075 | .0380 | 69.7% | 8.2 |
| 24 | .0075 | .0342 | 67.2% | 8.8 |
| 26 | .0075 | .0310 | 64.8% | 9.5 |
| 28 | .0075 | .0282 | 62.4% | 10.3 |
| 30 | .0065 | .0268 | 64.8% | 8.4 |
| 32 | .0065 | .0248 | 62.7% | 9.0 |
| 34 | .0065 | .0229 | 60.7% | 9.6 |
| 36 | .0065 | .0213 | 58.7% | 10.2 |
| 38 | .0065 | .0198 | 56.7% | 10.7 |
| 40 | .0065 | .0185 | 54.8% | 11.3 |
| 42 | .0055 | .0183 | 59.1% | 8.5 |
| 44 | .0055 | .0172 | 57.4% | 8.9 |
| 46 | .0055 | .0162 | 55.8% | 9.3 |
| 48 | .0055 | .0153 | 54.2% | 9.7 |
| 50 | .0055 | .0145 | 52.6% | 10.1 |
| 52 | .0055 | .0137 | 51.0% | 10.5 |
| 54 | .0055 | .0130 | 49.4% | 10.9 |
| 58 | .0045 | .0127 | 54.6% | 7.8 |
| 60 | .0045 | .0122 | 53.3% | 8.1 |
| 62 | .0045 | .0116 | 51.7% | 8.4 |
| 64 | .0045 | .0111 | 50.7% | 8.7 |
| 70 | .0037 | .0106 | 54.9% | 6.0 |
| 72 | .0037 | .0102 | 53.8% | 6.2 |
| 74 | .0037 | .0098 | 52.7% | 6.4 |
| 76 | .0037 | .0095 | 51.7% | 6.6 |
| 78 | .0037 | .0091 | 50.6% | 6.8 |



HOWARD WIRE CLOTH CO.

Stainless Steel Bolting Cloth

| Mesh Per Linear Inch | Wire Diameter Inches | Width of Opening Inches | Open Area Percent | Weight LBS./ 100 SQ. FT. |
|----------------------|----------------------|-------------------------|-------------------|--------------------------|
| 80 | .0037 | .0088 | 49.6% | 6.9 |
| 84 | .0035 | .0084 | 49.8% | 6.9 |
| 88 | .0035 | .0079 | 47.9% | 7.2 |
| 90 | .0035 | .0076 | 46.8% | 7.3 |
| 94 | .0035 | .0071 | 45.0% | 7.7 |
| 105 | .0030 | .0065 | 46.9% | 6.3 |
| 120 | .0025 | .0058 | 49.0% | 5.0 |
| 135 | .0023 | .0051 | 47.4% | 4.8 |
| 145 | .0022 | .0047 | 46.4% | 4.9 |
| 165 | .0019 | .0042 | 47.1% | 4.2 |
| 200 | .0016 | .0034 | 46.2% | 3.4 |
| 230 | .0014 | .0029 | 46.0% | 3.0 |